

GB

1 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 15.05.2009 Replaces the version of: 13.05.2005 PDF date: 18.05.2009
 PAOIL68 PLUS UV (PL68) 20.000 ml Art. Nr.: 8FX 351 214-241

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

PAOIL68 PLUS UV (PL68) 20.000 ml
Art. Nr.: 8FX 351 214-241

Use of the substance/preparation

Synthetic refrigerating system lubrication oil for vehicle air conditioners
 with fluorescent leak-tracing dye

Company/undertaking identification

Behr Hella Service GmbH, Dr.-Manfred-Behr-Str. 1, D-74523 Schwäbisch Hall
 Telephone +49 (0) 7907 9446 373 31, Fax +49 (0) 7907 9446 373 79

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

Emergency telephone

Advisory office in case of poisoning:

Tel.:
 +49 228 / 19240

Telephone number of the company in case of emergencies:

Tel. +49 (0) 7907 9446 373 31

2. HAZARDS IDENTIFICATION

To people

See point 11 and 15.
 Preparation is not classified as hazardous in the sense of directive 1999/45/EC.

To the environment

See point 12.
 n.av.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Polyolefin

Chemical name			
content %	Symbol	R-phrases	EINECS, ELINCS
	Registration number (ECHA)	DNEL	PNEC
--			

4. FIRST AID MEASURES

4.1 Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

4.2 Eye contact

GB

2 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision: 15.05.2009 Replaces the version of: 13.05.2005 PDF date: 18.05.2009

PAOIL68 PLUS UV (PL68) 20.000 ml Art. Nr.: 8FX 351 214-241

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

4.3 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

4.4 Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.5 Special resources necessary for first aid

Indications for the physician:

Symptomatic treatment

Ingestion:

Danger of aspiration

5. FIRE-FIGHTING MEASURES**5.1 Suitable extinguishing media**

Dry extinguisher

Alcohol resistant foam

Water jet spray

Cool container at risk with water.

5.2 Extinguishing media which shall not be used for safety reasons

High volume water jet

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Fume

Oxides of carbon

Toxic pyrolysis products.

5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

6. ACCIDENTAL RELEASE MEASURES

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods for cleaning up

Collect using absorbant material (e.g. Universal binding medium, sand, kieselguhr) and dispose of according to point 13.

7. HANDLING AND STORAGE**7.1 Handling****Tips for safe handling:**

See point 6.1

Ensure good ventilation.

Avoid aerosol formation.

Wash hands before breaks and at end of work.

GB

3 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 15.05.2009 Replaces the version of: 13.05.2005 PDF date: 18.05.2009
 PAOIL68 PLUS UV (PL68) 20.000 ml Art. Nr.: 8FX 351 214-241

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 General hygiene measures for the handling of chemicals are applicable.
 Observe directions on label and instructions for use.
 Do not heat to temperatures close to flash point.

7.2. Storage

Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Remove possible causes of ignition - do not smoke.

Special storage conditions:

See point 10
 Protect against moisture and store closed.
 Protect from direct sunlight and warming.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure limit values

8.2 Exposure controls

8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.

Respiratory protection:	Normally not necessary.
If fumes build up, use suitable breathing mask.	
Filter A P 3 (EN 14387)	
Hand protection:	Chemical resistant protective gloves (EN 374).
If applicable	
Protective Neopren gloves (EN 374).	
Protective nitrile gloves (EN 374)	
Protective gloves made of polyvinyl alcohol (EN 374)	
Protective PVC gloves (EN 374)	
Permeation time (penetration time) in minutes:	
> 360	
Protective hand cream recommended.	
Eye protection:	With danger of contact with eyes.
Tight fitting protective goggles with side protection (EN 166).	
Skin protection:	Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.
 Selection made for preparations according to the best available knowledge and information on the ingredients.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.2 Environmental exposure controls

n.av.

GB

4 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 15.05.2009 Replaces the version of: 13.05.2005 PDF date: 18.05.2009
 PAOIL68 PLUS UV (PL68) 20.000 ml Art. Nr.: 8FX 351 214-241

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous, Liquid
Colour:	Green, Yellow
Odour:	Mild
pH-value undiluted:	n.av.
Boiling point/boiling range (°C):	n.av.
Melting point/melting range (°C):	- 63 - - 54 (Pourpoint) (ASTM D97)
Flash point (°C):	> 200 (PMC) (ASTM D93)
Minimum limit of explosion:	n.a.
Maximum limit of explosion:	n.a.
Vapour pressure:	n.c.
Density (g/ml):	0,828 - 0,843 (15°C) (ASTM D1298)
Water solubility:	Insoluble
Viscosity:	30,7 - 99,6 cSt (40°C), 5,76 - 14,0 cSt (100°C) (ASTM D445)

10. STABILITY AND REACTIVITY

Conditions to avoid

See point 7
 Stable when handled and stored correctly.
 Product is combustible.
 Open flame, ignition sources

Materials to avoid

See point 7
 Avoid contact with strong oxidizing agents.

Hazardous decomposition products

See point 5.3

11. TOXICOLOGICAL INFORMATION

Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	n.av.
Skin contact, LD50 rat dermal (mg/kg):	n.av.
Eye contact:	n.av.

Delayed and chronic effects

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	n.c.

Further information

No classification according to calculation procedure.
 The following may occur:
 Watering eyes
 With long-term contact:
 Dermatitis (skin inflammation)
 Allergic reaction possible.
 Ingestion of large quantities:
 Vomiting
 Diarrhoea
 On vapour formation:
 Irritant to mucosa of the nose and throat

12. ECOLOGICAL INFORMATION

GB

5 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 15.05.2009 Replaces the version of: 13.05.2005 PDF date: 18.05.2009
 PAOIL68 PLUS UV (PL68) 20.000 ml Art. Nr.: 8FX 351 214-241

Water hazard class (Germany):	2
Self classification:	Yes (VwVwS)
Persistence and degradability:	n.av.
Behaviour in sewage plants:	
Mechanical precipitation possible.	
Aquatic toxicity:	
Hydrocarbons can be harmful to water.	
Ecological toxicity:	n.av.
Mobility:	
Endangerment of potable water possible.	
Accumulation:	
Concentration in organisms possible.	

13. DISPOSAL CONSIDERATIONS

13.1. for the material / preparation / residue

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

13 02 06 synthetic engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

15 01 01 paper and cardboard packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

14. TRANSPORT INFORMATION

General statements

UN-Number: n.a.

Road/Rail-transport (ADR/RID)

Class/packing group: n.a.

Classification code: n.a.

LQ: n.a.

Transport by sea

IMDG-code: n.a. (class/packing group)

Marine Pollutant: n.a.

Transport by air

IATA: n.a. (class/secondary danger/packing group)

Additional information:

Non-dangerous material according to Transport Regulations.

15. REGULATORY INFORMATION

Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)

GB

6 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 15.05.2009 Replaces the version of: 13.05.2005 PDF date: 18.05.2009
 PAOIL68 PLUS UV (PL68) 20.000 ml Art. Nr.: 8FX 351 214-241

Symbols:	Not applicable
Indications of danger:	---
R-phrases:	
S-phrases:	
Additions:	
Contains	
Tris-organo-trithiophosphate	
May produce an allergic reaction.	
Observe restrictions:	n.a.
VOC 1999/13/EC ---	

16. OTHER INFORMATION

These details refer to the product as it is delivered.

Storage class VCI (Germany):	10
Revised points:	1 - 16 REACH

Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked
 WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40
 AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)
 VbF = Regulations for flammable liquids (Austria)
 WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water
 VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds
 VwVwS = Administrative Order relating to substances hazardous to water (Germany)
 The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
 No responsibility.

These statements were made by:

Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.