



GB

1 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 29.05.2008 Replaces the version of: 18.08.2005 PDF date: 27.05.2010
Universal Dye 240 ml Art.: 8PE 351 225-171

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

Universal Dye 240 ml

Art.: 8PE 351 225-171

Use of the substance/preparation

Leak detector

Company/undertaking identification

Hella KGaA Hueck & Co, Rixbecker Str. 75, D-59552 Lippstadt
Telephone +49 (0) 2941 38 0, Fax +49 (0) 2941 38 7081
www.hella.de

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

Emergency telephone

Advisory office in case of poisoning:

Tel.:
+49 228 / 19240

Telephone number of the company in case of emergencies:

Tel. +49 (0) 2941 38 1562

2. HAZARDS IDENTIFICATION

To people

See point 11 and 15.
Preparation is not classified as hazardous in the sense of directive 1999/45/EC.
The following may occur:
Vapours may cause drowsiness and dizziness.

To the environment

n.av.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture of:
Dyes
Hydrocarbon mixture

Chemical name			
content %	Symbol	Chemical name	EINECS, ELINCS
	Registration number (ECHA)	Classification categories / Indications of danger:	
Solvent naphtha (petroleum), heavy arom.			
10 - 20	Xn	65-66-67 Harmful	265-198-5

For complete wording of the R-phrases / H-phrases (GHS/CLP), refer to point 16.

4. FIRST AID MEASURES

4.1 Inhalation

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 29.05.2008 Replaces the version of: 18.08.2005 PDF date: 27.05.2010
Universal Dye 240 ml Art.: 8PE 351 225-171

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

4.2 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.
Keep Data Sheet available.

4.4 Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting. Consult doctor immediately.
Danger of aspiration

4.5 Special resources necessary for first aid

n.c.

5. FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media

Foam
CO2
Water jet spray
Dry extinguisher
Cool container at risk with water.

5.2 Extinguishing media which shall not be used for safety reasons

n.c.

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:
Oxides of carbon
Toxic pyrolysis products.
Flammable vapour/air mixtures

5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply.

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

6. ACCIDENTAL RELEASE MEASURES

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.

6.3 Methods for cleaning up

Collect using absorbant material (e.g. Universal binding medium, sand, kieselguhr) and dispose of according to point 13.

7. HANDLING AND STORAGE

7.1 Handling

Tips for safe handling:

See point 6.1
Ensure good ventilation.
Avoid inhalation of the vapours.



GB

3 / 6
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 29.05.2008 Replaces the version of: 18.08.2005 PDF date: 27.05.2010
 Universal Dye 240 ml Art.: 8PE 351 225-171

Keep away from sources of ignition - Do not smoke.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Wash hands before breaks and at end of work.
 General hygiene measures for the handling of chemicals are applicable.
 Observe directions on label and instructions for use.

7.2. Storage

Requirements for storage rooms and containers:

Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.

Special storage conditions:

See point 10
 Protect against moisture and store closed.
 Protect from direct sunlight and warming.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure limit values

Chemical Name	Solvent naphtha (petroleum), heavy arom.	Content %:10 - 20
WEL-TWA: 500 mg/m3 (aromatics) (WEL), 100 mg/m3 (AGW)	WEL-STEL: 2(II) (AGW)	---
BMGV: ---	Other information: ---	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Respiratory protection: If OES or MEL is exceeded.
 Gas mask filter A (EN 14387)
 Hand protection: Solvent resistant protective gloves (EN 374).
 If applicable
 Protective Neopren gloves (EN 374).
 Protective nitrile gloves (EN 374)
 Protective hand cream recommended.
 Eye protection: Tight fitting protective goggles with side protection (EN 166).
 Skin protection: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.
 Selection made for preparations according to the best available knowledge and information on the ingredients.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 29.05.2008 Replaces the version of: 18.08.2005 PDF date: 27.05.2010
Universal Dye 240 ml Art.: 8PE 351 225-171

requested from the protective glove manufacturer and must be observed.

8.2.2 Environmental exposure controls

n.av.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 General information

Physical state: Liquid
Colour: Light brown, Yellow
Odour: Aromatic

9.2. Important health, safety and environmental information

pH-value undiluted: n.av.
Boiling point/boiling range (°C): 217 - 293
Melting point/melting range (°C): n.av.
Flash point (°C): 88 cc
Flammability (solid, gas): n.c.
Density (g/ml): 0,97
Water solubility: Insoluble
Vapour density (air = 1): > 1
Viscosity: 52,6 mm²/sec/40°C (DIN 51562), 45sec/4mm/20°C (DIN 53211)

10. STABILITY AND REACTIVITY

Conditions to avoid

See point 7
Stable when handled and stored correctly.

Materials to avoid

Avoid contact with strong oxidizing agents.
Avoid contact with strong acids.

Hazardous decomposition products

See point 5.3
No decomposition when used as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg): > 2000
Inhalation, LC50 rat inhal.(mg/l/4h): n.av.
Skin contact, LD50 rat dermal (mg/kg): n.av.
Eye contact: n.av.

Delayed and chronic effects

Sensitization: n.c.
Carcinogenicity: n.c.
Mutagenicity: n.c.
Reproductive toxicity: n.c.
Narcosis: Possible

Further information

No classification according to calculation procedure.

The following may occur:

Irritation of the eyes
On vapour formation:
Irritation of the respiratory tract
Headaches
Dizziness
Nausea
Effect on the central nervous system
Unconsciousness
With long-term contact:



GB

5 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 29.05.2008 Replaces the version of: 18.08.2005 PDF date: 27.05.2010
Universal Dye 240 ml Art.: 8PE 351 225-171

Drying of the skin.
Dermatitis (skin inflammation)

12. ECOLOGICAL INFORMATION

Persistence and degradability:	n.av.
Behaviour in sewage plants: According to the recipe, contains no AOX.	
Aquatic toxicity:	n.av.
Ecological toxicity:	n.av.
Mobility:	n.av.
Accumulation:	n.av.
Results of PBT assessment n.av.	
Other adverse effects:	n.av.

13. DISPOSAL CONSIDERATIONS

13.1. for the material / preparation / residue

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)
07 03 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Pay attention to local and national official regulations
E.g. suitable incineration plant.

13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

15 01 04 metallic packaging

15 01 02 plastic packaging

15 01 01 paper and cardboard packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

14. TRANSPORT INFORMATION

General statements

UN-Number: n.a.

Road/Rail-transport (ADR/RID)

Class/packing group: n.a.

Classification code: n.a.

LQ: n.a.

Tunnel restriction code:

Transport by sea

IMDG-code: n.a. (class/packing group)

Marine Pollutant: n.a.

Transport by air

IATA: n.a. (class/secondary danger/packing group)

Additional information:

Non-dangerous material according to Transport Regulations.

15. REGULATORY INFORMATION

**Classification according to Dangerous Product Regulations incl. EC Directives
(67/548/EEC and 1999/45/EC)**



GB

6 / 6

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 29.05.2008 Replaces the version of: 18.08.2005 PDF date: 27.05.2010
Universal Dye 240 ml Art.: 8PE 351 225-171

Symbols: Not applicable
Indications of danger: --
R-phrases:
67 Vapours may cause drowsiness and dizziness.
S-phrases:
Additions:
Safety data sheet available for professional user on request.
Observe restrictions: n.a.
VOC CH 16%

16. OTHER INFORMATION

These details refer to the product as it is delivered.
Storage class VCI (Germany): 3B
Revised points: 1 - 16 (REACH)
The following phrases represent the prescribed R-phrases / H-phrases (GHS/CLP) for the ingredients (designated in point 3).
65 Harmful: may cause lung damage if swallowed.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked
WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40
AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)
VbF = Regulations for flammable liquids (Austria)
WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water
VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds
VwVwS = Administrative Order relating to substances hazardous to water (Germany)
The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.
These statements were made by:
Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455
© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.